



A.T. Monitors

A leader in leak detection and level monitoring equipment

ATI-5100 Leak/Level Monitor

The ATI-5100 is a full service monitor designed to interface with any Normally Open or Closed liquid sensors and notify you of any leaks or spills immediately. The real-time response of the ATI-5100 allows you to avoid costly cleanups or interruptions in service, helping to protect your investment and the environment. The 12-channel, intrinsically safe (IS) capability offers flexibility at a price point that is rarely found among comparable products on the market.

Liquid Detection Circuit Board

Each sensor is wired to a numbered channel. When liquid makes contact with a sensor, the assigned channel goes into alarm. This causes the channel's LED to light up and sound an alarm for the attendant on duty.

Monitoring Capability: 12 channels/zones capable of monitoring any number of sensors in each zone.

Protection Circuit: Diode/resistor/fuse IS barrier on each channel.

Detectable Liquids: Refer to sensor data sheets for types of liquids.

Indicators and Alarms

Power Indicator: Green LED.

Battery Low Indicator: Yellow LED.

Liquid Alarm Indicators: 12 Red LEDs.

Audio Alarm Buzzer: 90dB @ 10cm, 3.6kHz, continuous for alarms and intermittent for battery low.

Alarm Acknowledge Switch: External pushbutton on right side.

Alarm Reset Switch: Pushbutton on front panel.

Relay Circuit Board

The ATI-5100 has 12 relays which can provide notification of critical conditions about liquid leaks to remote locations and control pumps, dispensers or any other external device.

Relays: 12 SPDT relays rated for 1 Amp max.

Contacts: Relays are jumper-selectable for Normally Open or Normally Closed.

Alarm Acknowledge Switch

The acknowledge button silences the alarm buzzer but leaves the LED indicator on to remind the attendant of a potential leak or alarm level. If no action is taken within two hours, the alarm buzzer will sound again, until the situation is resolved and reset button is pressed.

Alarm Reset Switch

The reset button is used to return the monitor to normal operating mode after an alarm condition. Even if the alarm condition disappears before corrective action is taken, this button must still be reset. This is designed to keep the lock-box key holder informed of all problems and to prevent the attendant from tampering with a sensor without first giving a qualified maintenance person the opportunity to investigate the situation.



IMPORTANT: All Armstrong Technologies Inc products should be used in compliance with applicable federal, provincial, state and local laws and regulations. Product selection should be based on physical specifications and limitations and compatibility with the environment and materials to be handled. **Armstrong Technologies MAKES NO WARRANTY OF FITNESS FOR A PARTICULAR USE.** All information and specifications in this literature are based on the latest product data available at the time of publication. Armstrong Technologies reserves the right to make changes at any time in prices, materials, specifications and to discontinue products without notice or obligation.



A.T. MONITORS
A division of Armstrong Technologies Inc.

14 Birch Drive
Kemptville, Ontario
K0G 1J0, CANADA

Phone: 613-258-5225
Fax: 613-258-2698
E-mail: info@atmonitors.com
Internet: www.atmonitors.com

Lock Box

A security feature designed to discourage tampering with circuits or the "Reset Alarms" switch.

Built-in Battery Backup

The battery backup option ensures the system will continue to function when primary power is temporarily lost. The battery life, with all three batteries installed, will exceed 100 hours under normal conditions.

Batteries: Up to 3 Gel-Cells, 12VDC/1.2AH each.

Battery Low Indicator: Yellow LED.

Audio Alarm: Intermittent beeping once every minute when the batteries are at a critically low voltage.

Mounting and Accessibility

The ATI-5100 can be mounted under counters, in kiosks or other small area for ease of access and visibility to the attendant.

Power Requirements

Main Power: 120VAC, 60Hz @ 1A max.

Fuse Type and Rating: AGX 2 Amp or equivalent.

Dimensions

H 9.3"/22.5cm x W 13"/31cm x D 6.8"/18.5cm.

Enclosure Material: ABS and Polycarbonate.

Operating Temperature Range

Ambient: 0 to +60 °C (+32 to 140 °F).

Warranty

One (1) year, parts and labour, subject to standard Armstrong Technologies' terms and conditions.

COMPATIBLE SENSORS

5005 Series Water Sensors

5007B – Dual Liquid Sensing Cable

5008 – Vacuum Sensor

5010 – Liquid Level Float Sensors

5010S – Sump Brine Sensor

5010W – Interstitial Leak Sensor

5016 Series Petroleum Sensors

5025 – Water Detection Cable

REMOTE ALARM



For monitoring and acknowledging at non-hazardous remote location, A.T.Monitors offers the **ATI-RAM1-RLV**.

For more information, visit www.atmonitors.com or talk to a qualified agent.